



Dew point and temperature probe DMP5

For dew point measurement in high temperatures up to 180 °C

| | | Probe head and cable | Probe cable | Sensor type | Filter type | Operating pressure | Baud rate | Parity, data bit, stop bit | Probe Modbus address | Reserved | Probe mounting accessory | Connection cable |
|----|--|----------------------|-------------|-------------|-------------|--------------------|-----------|----------------------------|-----------------------|----------|--------------------------|------------------|
| | | DMPX | 5 | 1 | A | 0 | | | | 0 | | |
| 1 | Probe head and cable DMP5 for high temperatures | 5 | | | | | | | | | | |
| 2 | Probe cable Probe 5, 2m Probe 5, 10m | | A B | | | | | | | | | |
| 3 | Sensor type DrycapS | | | 1 | | | | | | | | |
| 4 | Filter type Sintered stainless steel filter | | | | A | | | | | | | |
| 5 | Operating pressure Setting for ppm and other calculated variables 1) 1 bar (absolute) | | | | | 0 | | | | | | |
| 6 | Baud rate 1) 19200 9600 | | | | | | A B | | | | | |
| 7 | Parity, data bit, stop bit 1) 8,N,2 8,E,1 8,O,1 | | | | | | | 0 2 4 | | | | |
| 8 | Probe Modbus address 1) 240 110 120 130 140 | | | | | | | | A B C D E | | | |
| 9 | Reserved None | | | | | | | | | 0 | | |
| 10 | Probe mounting accessory None (installation into existing mounting flange) Mounting flange | | | | | | | | | | 0 A | |
| 11 | Connection cable None 1,5m, open ends 10m, open ends | | | | | | | | | | | 0 1 2 |

1) Factory pre-set, can be changed in the field with a service cable (P/N 242659)

Probe can be connected to INDIGO series of transmitters regardless of the output configuration.

Selections in bold are included in the prices of the basic versions.

Selections in italic are available at an extra price.

Example of order code with typical settings:

| | | | | | | | | | | | | |
|----------------------------------|------|---|---|---|---|---|---|---|---|---|---|---|
| For use with INDIGO transmitters | DMPX | 5 | A | 1 | A | 0 | A | 0 | A | 0 | A | 0 |
| For use with Modbus RTU | DMPX | 5 | A | 1 | A | 0 | A | 0 | A | 0 | A | 2 |

Valid from: December 2019